

FLOOR PAINT THINNERS

SPO/V607/14

DESCRIPTION:

SPO Floor Paint Thinners is a Hydrocarbon solvent.

RECOMMENDED USE:

SPO Floor Paint Thinners is used to thin and clean down SPO Floor Paint. (Not for use with SPO High Performance Floor Paint)

AVAILABILITY:

2.5 litre

FINISH:

N/A

COLOUR:

Clear thin liquid.

TYPICAL S.G. (SPECIFIC GRAVITY):

0.79 @ 20 °C

VOLUME SOLIDS:

N/A

WET FILM THICKNESS W.F.T

N/A

DRY FILM THICKNESS D.F.T

N/A

EXPECTED SPREADING RATE:

N/A

N/A

The practical spreading rate may be lower as this depends on factors such as the porosity and roughness of the surface to be painted and material losses during application.

TYPICAL VISCOSITY:

N/A

FLASH POINT:

40 °C (closed cup)

DRYING TIME: @ RECOMMENDED D.F.T

Touch dry: N/A

Hard dry: N/A

Full hardness: N/A

Low temperature and high humidity will adversely affect application, drying and performance of any coating.

MINIMUM OVERCOATING TIME:

N/A

APPLICATION SPECIAL CONDITIONS:

N/A

VOC CONTENT:

N/A

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution

APPLICATION DETAILS:

Application N/A
restrictions

Method: N/A

Thinner N/A
(Max vol):

Nozzle size: N/A

Nozzle N/A
pressure:

Cleaning N/A
solvent:

Recoat N/A
interval:

SURFACE PREPARATION:

N/A

**For further advice contact SPO Technical Services at
sales@specialistpaintsonline.co.uk**
The physical constants are subject to normal manufacturing tolerances.

FLOOR PAINT THINNERS**SPO/V607/14**

MIXING INSTRUCTIONS:

N/A

APPLICATION CONDITIONS:

N/A

PRECEDING COAT:

N/A

SUBSEQUENT COAT:

N/A

REMARKS:

Flamability limits in air:- Lower - 1% by volume
Upper - 6% by volume

Vapour pressure:- 0.8mm HG @ 20°C

HEALTH AND SAFETY:

See safety data sheet - SDS 11252

ISSUED:

25 October 2010

REVISION:

1

The information given in this data sheet is based on experience and is accurate to the best of our knowledge. No guarantee should be implied, however, as the conditions of use are beyond our control. This data sheet does not constitute a specification. In case of doubt as to the suitability of the product please contact our Technical Service Department at sales@specialistpaintsonline.co.uk

**For further advice contact SPO Technical Services at
sales@specialistpaintsonline.co.uk
The physical constants are subject to normal manufacturing tolerances.**

3 Kirkby Street
Hull HU2 0HE
Tel.: +44(0)1482 222421

Email: sales@specialistpaintsonline.co.uk
www.specialistpaintsonline.co.uk