

OIL REMOVER**DESCRIPTION:**

SPO Oil Remover is an efficient cleaner designed to provide rapid release of oil and hydrocarbon contamination from floors, walls and other substrates.

RECOMMENDED USE:

SPO Oil Remover is an aqueous cleaner designed for use on floors, walls and other hard surfaces. It rapidly releases heavy oils, hydrocarbons and ground-in dirt from surfaces such as concrete, brick and breezeblock. Use to deep clean floor surfaces prior to the application of coatings, seals and other finishes. Also use to remove slip hazards following leaks and spills.

AVAILABILITY:

2.5 litres

FINISH:

N/A

COLOUR:

Golden liquid

TYPICAL S.G. (SPECIFIC GRAVITY):

1.01 @ 20 °C

VOLUME SOLIDS:

N/A

WET FILM THICKNESS W.F.T**DRY FILM THICKNESS D.F.T****EXPECTED SPREADING RATE:**

1 - 2 sq.m / litre

N/A

The practical spreading rate may be lower as this depends on factors such as the porosity and roughness of the surface to be painted and material losses during application.

TYPICAL VISCOSITY:

N/A

FLASH POINT:

N/A

DRYING TIME: @ RECOMMENDED D.F.T

Touch dry: N/A

Hard dry: N/A

Full hardness: N/A

Low temperature and high humidity will adversely affect application, drying and performance of any coating.

MINIMUM OVERCOATING TIME:

N/A

APPLICATION SPECIAL CONDITIONS:

Oil remover is supplied ready for use. Protect from frost.

VOC CONTENT:

0 g / litre

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution

APPLICATION DETAILS:

Application restrictions

Method: Apply manually or use a back pack spray system

Thinner (Max vol):

Nozzle size:

Nozzle pressure:

Cleaning solvent:

For further advice contact SPO Technical Services at sales@specialistpaintsonline.co.uk

The physical constants are subject to normal manufacturing tolerances.

OIL REMOVER

Recoat N/A
interval:

SURFACE PREPARATION:

Sweep floor to remove debris.

MIXING INSTRUCTIONS:

Supplied ready for use

APPLICATION CONDITIONS:

Apply liberally to the area to be cleaned. Work well into the surface with a stiff brush and leave for 20 to 60 minutes. Rinse the area well with a pressure washer or hose, collect the rinse water with a wet vac machine. Once the surface oil contamination has been removed, continue with any surface preparation as necessary i.e. mechanical abrasion or chemical etching as required to provide a key for a subsequent coating.

PRECEDING COAT:

n/a

SUBSEQUENT COAT:

Allow the surface to dry thoroughly. This can take up to several days.

REMARKS:

Oil remover contains no dangerous caustic chemicals, harmful solvents, phosphates or aggressive biocides. It is safer for the user and the environment.

Shelf Life: 12 Months in original container

HEALTH AND SAFETY:

See SDS 11238

ISSUED:

27 May 2010

REVISION:

0

The information given in this data sheet is based on experience and is accurate to the best of our knowledge. No guarantee should be implied, however, as the conditions of use are beyond our control. This data sheet does not constitute a specification. In case of doubt as to the suitability of the product please contact our Technical Service Department at sales@specialistpaintsonline.co.uk

**For further advice contact SPO Technical Services at
sales@specialistpaintsonline.co.uk**

The physical constants are subject to normal manufacturing tolerances.

3 Kirkby Street
Hull HU2 0HE
Tel.: +44(0)1482 222421

Email: sales@specialistpaintsonline.co.uk
www.specialistpaintsonline.co.uk