



SAFETY DATA SHEET
SPO/W224 - ANTI BACTERIAL PAINT HARDENER FOR GREEN

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name SPO/W224 - ANTI BACTERIAL PAINT HARDENER FOR GREEN
Product No. SPO/W224/15 - hardener for green

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses HARDENER FOR TWO COMPONENT FLOOR COATING

1.3. Details of the supplier of the safety data sheet

Supplier SPECIALIST PAINTS ONLINE
3 KIRKBY STREET
HULL
HU2 0HE
+44 (0) 1482 222421 (T)
sales@specialistpaintsonline.co.uk
Contact Person Sales Department - 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri as above

1.4. Emergency telephone number

+44 (0) 1482 222421 - Specialist Paints Online (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)
Physical and Chemical Hazards Not classified.
Human health Not classified.
Environment Not classified.

Classification (1999/45/EEC) Not classified.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Human health

The product contains a small amount of sensitising substance which may provoke an allergic reaction among sensitive individuals in contact with skin.

Physical and Chemical Hazards

When handled correctly, undamaged units represent no danger.

2.2. Label elements

Label In Accordance With (EC) No. 1272/2008

No pictogram required.

Precautionary Statements

P102	Keep out of reach of children.
P101	If medical advice is needed, have product container or label at hand.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P501A	Dispose of contents/container to special waste collection point

Supplemental label information

EUH205	Contains epoxy constituents. May produce an allergic reaction.
--------	--

SPOW224 - ANTI BACTERIAL PAINT HARDENER FOR GREEN

EUH208

Contains

3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE,m-phenylenebis(methylamine). May produce an allergic reaction.

2.3. Other hazards**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS****3.2. Mixtures**

Barium Sulphate			1-5%
CAS-No.: 7727-43-7	EC No.: 231-784-4	Registration Number: 01-2119491274-35-0001	
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.		
Calcium Magnesium Silicate			1-5%
CAS-No.: 14807-96-6	EC No.: 238-877-9		
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.		
3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE			<1%
CAS-No.: 2855-13-2	EC No.: 220-666-8		
Classification (EC 1272/2008) Acute Tox. 4 - H302 Acute Tox. 4 - H312 Skin Corr. 1B - H314 Skin Sens. 1 - H317 Aquatic Chronic 3 - H412	Classification (67/548/EEC) C;R34 Xn;R21/22 R43 R52/53		
m-phenylenebis(methylamine)			<1%
CAS-No.: 1477-55-0	EC No.: 216-032-5	Registration Number: 01-2119480150-50	
Classification (EC 1272/2008) Acute Tox. 4 - H302 Acute Tox. 3 - H331 Skin Corr. 1B - H314 Skin Sens. 1 - H317 Aquatic Chronic 3 - H412	Classification (67/548/EEC) Xn;R20/22. C;R34. R43,R52/53.		
3-(Polyoxyethylene)propylheptamethyltrisiloxane			<1%
CAS-No.: 67674-67-3	EC No.:		
Classification (EC 1272/2008) Acute Tox. 4 - H332 Eye Dam. 1 - H318 Aquatic Chronic 2 - H411	Classification (67/548/EEC) Xn;R20. Xi;R41. N;R51/53.		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SPOW224 - ANTI BACTERIAL PAINT HARDENER FOR GREEN**SECTION 4: FIRST AID MEASURES****4.1. Description of first aid measures**

General information

General first aid, rest, warmth and fresh air. Do not give victim anything to drink if they are unconscious.

Inhalation

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

Ingestion

Immediately rinse mouth and drink plenty of water. If person becomes uncomfortable or if ingested in large amounts (50-100 ml for an adult person): Take to hospital along with these instructions. Do not induce vomiting. NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS!

Skin contact

Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.

Eye contact

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Continue flushing during transport to hospital. Bring these instructions.

4.2. Most important symptoms and effects, both acute and delayed

General information

If adverse symptoms develop as described the casualty should be transferred to hospital as soon as possible.

4.3. Indication of any immediate medical attention and special treatment needed

No recommendation given, but first aid may still be required in case of accidental exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY!

SECTION 5: FIREFIGHTING MEASURES**5.1. Extinguishing media**

Extinguishing media

This product is not flammable.

5.2. Special hazards arising from the substance or mixture

Specific hazards

The product is non-combustible. If heated, harmful vapours may be formed.

5.3. Advice for firefighters

Special Fire Fighting Procedures

Keep run-off water out of sewers and water sources. Dike for water control. Avoid breathing fire vapours.

Protective equipment for fire-fighters

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures**

Exclude non-essential personnel. Wear protective clothing as described in Section 8 of this safety data sheet. Avoid inhalation of vapours and contact with skin and eyes.

6.2. Environmental precautions

Avoid discharge to the aquatic environment. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Stop leak if possible without risk. Neutralise with dilute aqueous acid, such as acetic acid. Neutralisation reaction is exothermic. Flush with plenty of water to clean spillage area. Do not contaminate water sources or sewer. For waste disposal, see section 13.

6.4. Reference to other sections

For personal protection, see section 8.

SPOW224 - ANTI BACTERIAL PAINT HARDENER FOR GREEN**SECTION 7: HANDLING AND STORAGE****7.1. Precautions for safe handling**

Avoid inhalation of vapours/spray and contact with skin and eyes. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Persons with a history of skin sensitisation problems should not be employed in a situation where skin contact with this product could occur, nor should those with asthma or similar disorders be exposed to the vapour or spray mist. The Manual Handling Operations Regulations may apply to the handling of containers of this product. To assist employers, the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight.

7.2. Conditions for safe storage, including any incompatibilities

Keep upright. Store in tightly closed original container in a dry and cool place.

Storage Class

Chemical storage.

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters**

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
Barium Sulphate	WEL		10 mg/m ³			
Calcium Magnesium Silicate	WEL		1 mg/m ³			

WEL = Workplace Exposure Limit.

3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE (CAS: 2855-13-2)

DNEL			
Professional	Inhalation.	20.1	mg/m ³
PNEC			
Professional	Freshwater	0.06	mg/l
Professional	Marinewater	0.006	mg/l

8.2. Exposure controls

Protective equipment



Engineering measures

Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours.

Respiratory equipment

If ventilation is insufficient, suitable respiratory protection must be provided.

Hand protection

Use suitable protective gloves if risk of skin contact. Neoprene, nitrile, polyethylene or PVC. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

Eye protection

Wear splash-proof eye goggles to prevent any possibility of eye contact.

Other Protection

Wear appropriate clothing to prevent reasonably probable skin contact. Provide eyewash station.

Hygiene measures

Wash hands at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke.

SPOW224 - ANTI BACTERIAL PAINT HARDENER FOR GREEN**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES****9.1. Information on basic physical and chemical properties**

Appearance	Viscous Liquid
Colour	Yellowish
Odour	Ammonia.
Solubility	Soluble in water.
Initial boiling point and boiling range (°C)	>100 760 mm Hg
Relative density	1.27 @ 20 C
pH-Value, Conc. Solution	8.9
Viscosity	15000 - 25000 cP @ 25 C
Flash point (°C)	
Will not flash.	
Explosive properties	
Not applicable.	
Other Flammability	
Not applicable.	

9.2. Other information

Volatile Organic Compound (VOC) 0 g/litre

SECTION 10: STABILITY AND REACTIVITY**10.1. Reactivity**

No specific reactivity hazards associated with this product.

10.2. Chemical stability

Stable under normal temperature conditions and recommended use.

10.3. Possibility of hazardous reactions

Not determined.

10.4. Conditions to avoid

Avoid contact with acids and oxidising substances.

10.5. Incompatible materials**10.6. Hazardous decomposition products**

In case of fire, toxic gases (CO, CO₂, NO_x) may be formed.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects****Inhalation**

In high concentrations, vapours may irritate throat and respiratory system and cause coughing.

Ingestion

Irritating. May cause nausea, stomach pain and vomiting.

Skin contact

Irritating to skin. Risk of sensitisation or allergic reactions among sensitive individuals.

SPOW224 - ANTI BACTERIAL PAINT HARDENER FOR GREEN

Eye contact

Risk of serious damage to eyes. Irritating and may cause redness and pain.

Route of entry

Inhalation. Skin absorption. Ingestion. Skin and/or eye contact.

Toxicological information on ingredients.**3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE (CAS: 2855-13-2)**

Toxic Dose 1 - LD 50

1030 mg/kg (oral rat)

Acute toxicity:

Acute Toxicity (Dermal LD50)

1840 mg/kg Rat

3-(Polyoxyethylene)propylheptamethyltrisiloxane (CAS: 67674-67-3)**m-phenylenebis(methylamine) (CAS: 1477-55-0)**

Toxic Dose 1 - LD 50

930 mg/kg (oral rat)

Toxic Conc. - LC 50

2.4 mg/l/4h (inh-rat)

Acute toxicity:

Acute Toxicity (Dermal LD50)

2000 mg/kg Rabbit

Aspiration hazard:

Skin contact

Irritating to skin. May cause sensitisation by skin contact.

Irritation of eyes and mucous membranes. Risk of serious damage to eyes.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Dangerous for the environment if discharged into watercourses. The product contains a substance which may have adverse effects on waste water treatment processes. The product may affect the acidity (pH-factor) in water with risk of harmful effects to aquatic organisms.

12.1. ToxicityEcological information on ingredients.**3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE (CAS: 2855-13-2)**

LC50 96 hours 110 mg/l Brachydanio rerio (Zebra Fish)

EC 50, 48 Hrs, Daphnia, mg/l

23

Acute Toxicity - Aquatic Plants

EC50 72 hours 50 mg/l Scenedesmus subspicatus

m-phenylenebis(methylamine) (CAS: 1477-55-0)

Acute Toxicity - Fish

LC50 96 hours > 100 mg/l Brachydanio rerio (Zebra Fish)

LC50 96 hours > 100 mg/l Onchorhynchus mykiss (Rainbow trout)

Acute Toxicity - Aquatic Invertebrates

EC50 48 hours 16 mg/l Daphnia magna

Acute Toxicity - Aquatic Plants

EC50 72 hours 12 mg/l Scenedesmus subspicatus

12.2. Persistence and degradability**12.3. Bioaccumulative potential**

SPOW224 - ANTI BACTERIAL PAINT HARDENER FOR GREEN

Bioaccumulative potential

No data available on bioaccumulation.

Ecological information on ingredients.**m-phenylenebis(methylamine) (CAS: 1477-55-0)**

Bioaccumulation factor

BCF 2.69134803

Partition coefficient

log Pow 0.18

12.4. Mobility in soil

Mobility:

The product is partly miscible with water and may spread in the aquatic environment.

12.5. Results of PBT and vPvB assessment**12.6. Other adverse effects**

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

General information

Do not allow to enter drains, sewers or watercourses. Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements. Do not allow runoff to sewer, waterway or ground.

Environmental manager must be informed of all major spillages.

Waste Class

When this material, in its liquid state, as supplied, becomes a waste, it is categorised as a hazardous waste, with code 08 01 11* (EPOXY BASED LIQUID WASTE). Part-used containers, not drained and/or rigorously scraped out and containing residues of the supplied material, are categorised as hazardous waste, with code 08 01 11* (EPOXY BASED LIQUID WASTE). Neutralised empty packages, are categorised as non-hazardous waste, with code 15 01 02(plastic packaging) or 15 01 04 (metal packaging)

SECTION 14: TRANSPORT INFORMATION

General	The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).
---------	---

Sea Transport Notes	Not classified.
---------------------	-----------------

14.1. UN number**14.2. UN proper shipping name**

Proper Shipping Name	PAINT
----------------------	-------

14.3. Transport hazard class(es)

ADR/RID/ADN Class	Not classified for transportation.
-------------------	------------------------------------

IMDG Class	not classified
------------	----------------

14.4. Packing group**14.5. Environmental hazards**

Environmentally Hazardous Substance/Marine Pollutant

No.

14.6. Special precautions for user

SPOW224 - ANTI BACTERIAL PAINT HARDENER FOR GREEN**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

SECTION 15: REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Uk Regulatory References

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments.

Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). Control of Substances Hazardous to Health.

Approved Code Of Practice

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply. Dangerous Substances and Explosive Atmospheres Regulations 2002 [L138]

Guidance Notes

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

EU Legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

National Regulations

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689.

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION

Revision Comments

Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 453/2010 Update for CLP labelling.

Issued By	Technical Dept. (P.E.)
Revision Date	18/05/2015
Revision	3
Supersedes date	13/03/2013
SDS No.	11456
Safety Data Sheet Status	Approved.
Date	Date printed _____
Signature	Initials _____

Risk Phrases In Full

R34	Causes burns.
R20/22	Harmful by inhalation and if swallowed.
R20	Harmful by inhalation.
R21/22	Harmful in contact with skin and if swallowed.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R43	May cause sensitisation by skin contact.
NC	Not classified.
R41	Risk of serious damage to eyes.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SPOW224 - ANTI BACTERIAL PAINT HARDENER FOR GREEN

Hazard Statements In Full

H318	Causes serious eye damage.
H314	Causes severe skin burns and eye damage.
H332	Harmful if inhaled.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H412	Harmful to aquatic life with long lasting effects.
H317	May cause an allergic skin reaction.
H331	Toxic if inhaled.
H411	Toxic to aquatic life with long lasting effects.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.