



SAFETY DATA SHEET
SPO/W201 - METALS PRIMER - RED & GREY

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name SPO/W201 - METALS PRIMER - RED & GREY
Product No. SPO/W201/65 & 703

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Paint. Primer.

1.3. Details of the supplier of the safety data sheet

Supplier SPECIALIST PAINTS ONLINE
3 KIRKBY STREET
HULL
HU2 0HE
+44 (0) 1482 222421 (T)
sales@specialistpaintsonline.co.uk
Contact Person Sales Department - 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri as above

1.4. Emergency telephone number

+44 (0) 1482 222421 - Specialist Paints Online (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)
Physical and Chemical Hazards Not classified.
Human health Not classified.
Environment Not classified.
Classification (1999/45/EEC) Not classified.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

2.2. Label elements

Label In Accordance With (EC) No. 1272/2008
No pictogram required.

Precautionary Statements

P102	Keep out of reach of children.
P101	If medical advice is needed, have product container or label at hand.
P262	Do not get in eyes, on skin, or on clothing.
P271	Use only outdoors or in a well-ventilated area.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+313	If eye irritation persists: Get medical advice/attention.
P501A	Dispose of contents/container to special waste collection point

2.3. Other hazards

SPO/W201 - METALS PRIMER - RED & GREY

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Titanium Dioxide		5-10%
CAS-No.: 13463-67-7	EC No.: 236-675-5	Registration Number: 01-2119489379-17-xxxx
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.	
Monopropylene glycol		1-5%
CAS-No.: 57-55-6	EC No.: 200-338-0	Registration Number: 01-2119456809-23-xxxx
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.	
Barium Sulphate		<1%
CAS-No.: 7727-43-7	EC No.: 231-784-4	Registration Number: 01-2119491274-35-0001
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.	
Calcium Magnesium Silicate		<1%
CAS-No.: 14807-96-6	EC No.: 238-877-9	
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.	
DI-tert-(C12-14)-ALKYLAMMONIUM 2-BENZOTHAZOLYLTHIOSUCCINATE		<1%
CAS-No.: 125078-60-6	EC No.: 406-052-4	
Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Aquatic Chronic 2 - H411	Classification (67/548/EEC) R10 Xn;R22 Xi;R38,R41 N;R51/53	
Zinc naphthanate salts		<1%
CAS-No.: 68551-44-0	EC No.: 271-378-4	
Classification (EC 1272/2008) Skin Irrit. 2 - H315 Aquatic Chronic 2 - H411	Classification (67/548/EEC) Xi;R38. N;R51/53.	

SPO/W201 - METALS PRIMER - RED & GREY

2-METHOXY-1-METHYLETHYL ACETATE	<1%
CAS-No.: 108-65-6	EC No.: 203-603-9
Registration Number: 01-2119475791-29-xxxx	

Classification (EC 1272/2008) Flam. Liq. 3 - H226	Classification (67/548/EEC) R10
--	------------------------------------

Low Aromatic White Spirit	<1%
CAS-No.:	EC No.: 919-857-5
Registration Number: 01-2119463258-33-XXXX	

Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 STOT SE 3 - H336 Asp. Tox. 1 - H304	Classification (67/548/EEC) Xn;R65. R10,R66,R67.
--	--

AMMONIA ...%	<0.1%
CAS-No.: 1336-21-6	EC No.: 215-647-6

Classification (EC 1272/2008) Skin Corr. 1B - H314 STOT SE 3 - H335 Aquatic Acute 1 - H400	Classification (67/548/EEC) C;R34 N;R50
---	---

SODIUM HYDROXIDE	<0.1%
CAS-No.: 1310-73-2	EC No.: 215-185-5

Classification (EC 1272/2008) Skin Corr. 1A - H314	Classification (67/548/EEC) C;R35
---	--------------------------------------

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information

General first aid, rest, warmth and fresh air. Do not give victim anything to drink if they are unconscious.

Inhalation

Remove victim immediately from source of exposure. Provide rest, warmth and fresh air. Get medical attention if any discomfort continues. Place unconscious person on the side in the recovery position and ensure breathing can take place.

Ingestion

DO NOT induce vomiting. Get medical attention immediately. Provide fresh air, warmth and rest, preferably in comfortable upright sitting position.

Skin contact

Remove affected person from source of contamination. Remove contaminated clothing immediately and wash skin with soap and water.

Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information

If adverse symptoms develop as described the casualty should be transferred to hospital as soon as possible.

SPO/W201 - METALS PRIMER - RED & GREY**4.3. Indication of any immediate medical attention and special treatment needed**

No specific first aid measures noted.

SECTION 5: FIREFIGHTING MEASURES**5.1. Extinguishing media**

Extinguishing media

Extinguish with foam, carbon dioxide, dry powder or water fog. Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards

The product is non-combustible. If heated, corrosive and toxic vapours/gases may be formed.

5.3. Advice for firefighters

Special Fire Fighting Procedures

Avoid breathing fire vapours. Do not allow runoff to sewer, waterway or ground. Cool containers exposed to flames with water until well after the fire is out.

Protective equipment for fire-fighters

Selection of respiratory protection for fire fighting: follow the general fire precautions indicated in the workplace.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures**

Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Contain spillages with sand, earth or any suitable adsorbent material.

Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Should be prevented from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

6.4. Reference to other sections

For personal protection, see section 8.

SECTION 7: HANDLING AND STORAGE**7.1. Precautions for safe handling**

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Avoid inhalation of vapours and spray mists. Do not eat, drink or smoke when using the product. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. The Manual Handling Operations Regulations may apply to the handling of containers of this product.

To assist employers, the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight.

7.2. Conditions for safe storage, including any incompatibilities

Store in closed original container at temperatures between 5°C and 25°C. Keep away from heat, sparks and open flame. Protect from freezing and direct sunlight. Keep containers tightly closed. Keep upright. Store separated from: Oxidising material. Alkalis. Acids.

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

Usage Description

Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container.

SPO/W201 - METALS PRIMER - RED & GREY**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1. Control parameters**

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
2-METHOXY-1-METHYLETHYL ACETATE	WEL	50 ppm	274 mg/m3	100 ppm	548 mg/m3	Sk
AMMONIA ...%	WEL	25 ppm	35 mg/m3	17 ppm	24 mg/m3	
Barium Sulphate	WEL		10 mg/m3			
Calcium Magnesium Silicate	WEL		1 mg/m3			
Low Aromatic White Spirit	WEL		1000 mg/m3			
Monopropylene glycol	WEL	150 ppm	10 mg/m3			
SODIUM HYDROXIDE	WEL				2 mg/m3	
Titanium Dioxide	WEL		10 mg/m3			

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through skin.

SPO/W201 - METALS PRIMER - RED & GREY**2-METHOXY-1-METHYLETHYL ACETATE (CAS: 108-65-6)**

DNEL				
Professional	Dermal	Long Term	Systemic Effects	153.5 mg/kg/day
Professional	Inhalation.	Long Term	Systemic Effects	275 mg/m3
Consumer	Dermal	Long Term	Systemic Effects	54.8 mg/kg/day
Consumer	Inhalation.	Long Term	Systemic Effects	33 mg/m3
Consumer	Oral	Long Term	Systemic Effects	1.67 mg/kg/day
PNEC				
Freshwater	0.635	mg/l		
Marinewater	0.0635	mg/l		
Intermittent release	6.35	mg/l		
STP	100	mg/l		
Sediment	3.29	mg/kg		
Sediment (Marinewater)	0.329	mg/kg		
Soil	0.29	mg/kg		

Titanium Dioxide (CAS: 13463-67-7)

DNEL				
Industry	Inhalation.	Long Term	Local Effects	10 mg/m3
Consumer	Oral	Long Term	Systemic Effects	700 mg/kg/day
PNEC				
Freshwater	>1	mg/l		
Sediment (Freshwater)	>=1000	mg/kg		
Marinewater	0.127	mg/l		
Sediment (Marinewater)	>=100	mg/kg		
Soil	100	mg/kg		
STP	100	mg/kg		

Monopropylene glycol (CAS: 57-55-6)

DNEL				
Professional	Inhalation.	Long Term	Systemic Effects	50 mg/m3
Professional	Inhalation.	Long Term	Local Effects	10 mg/m3
Consumer	Inhalation.	Long Term	Systemic Effects	168 mg/m3
Consumer	Inhalation.	Long Term	Local Effects	10 mg/m3
PNEC				
Freshwater	206	mg/l		
Marinewater	26	mg/l		
Sediment (Freshwater)	572	mg/l		
Sediment (Marinewater)	57.2	mg/l		
Soil	50	mg/kg		
STP	20000	mg/l		

TEXANOL (CAS: 25265-77-4)

DNEL				
Oral	Long Term	8.3	mg/kg/day	
Professional	Inhalation.	Long Term	49	mg/m3
Consumer	Inhalation.	Long Term	14.5	mg/m3
Professional	Dermal	Long Term	13.9	mg/kg/day
Consumer	Dermal	Long Term	8.3	mg/kg/day
PNEC				
Freshwater	0.015	mg/l		
Marinewater	0.0015	mg/l		
Intermittent release	0.15	mg/l		
Sediment (Freshwater)	0.17	mg/kg		
Sediment (Marinewater)	0.017	mg/kg		
Soil	0.13	mg/kg		
STP	7.5	mg/l		

Low Aromatic White Spirit

DNEL				
Consumer	Oral	Long Term	Systemic Effects	300 mg/kg/day
Consumer	Dermal	Long Term	Systemic Effects	300 mg/kg/day
Industry	Dermal	Long Term	Systemic Effects	300 mg/kg/day
Industry	Inhalation.	Long Term	Systemic Effects	1500 mg/m3
Consumer	Inhalation.	Long Term	Systemic Effects	900 mg/m3

No PNEC available. Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for the risk assessment of this complex substance.

8.2. Exposure controls

Protective equipment

SPO/W201 - METALS PRIMER - RED & GREY**Engineering measures**

Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours.

Respiratory equipment

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

Hand protection

Use suitable protective gloves if risk of skin contact. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

Eye protection

Wear approved, tight fitting safety glasses where splashing is probable.

Other Protection

Wear appropriate clothing to prevent reasonably probable skin contact.

Hygiene measures

No specific hygiene procedures noted, but good personal hygiene practices are always advisable, especially when working with chemicals.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties**

Appearance	Viscous Coloured liquid.
Colour	Red. or Grey.
Odour	Slight odour.
Solubility	Soluble in water.
Relative density	approx. 1.16 @ 20C
Vapour density (air=1)	heavier than air
pH-Value, Conc. Solution	8.0 - 9.0
Viscosity	2.0 - 3.0 Ps @ 25C
Flash point (°C)	N/A

9.2. Other information

Volatile Organic Compound (VOC) 36 g/litre

SECTION 10: STABILITY AND REACTIVITY**10.1. Reactivity**

No specific reactivity hazards associated with this product.

10.2. Chemical stability

Stable under normal temperature conditions and recommended use.

10.3. Possibility of hazardous reactions

Not determined.

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with acids and oxidising substances.

10.5. Incompatible materials

Materials To Avoid

Strong alkalis. Strong acids. Strong oxidising substances.

10.6. Hazardous decomposition products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SPO/W201 - METALS PRIMER - RED & GREY**SECTION 11: TOXICOLOGICAL INFORMATION****11.1. Information on toxicological effects**

Toxicological information

No data recorded.

General information

No specific health warnings noted.

Inhalation

No specific health warnings noted.

Ingestion

No harmful effects expected in amounts likely to be ingested by accident.

Skin contact

Prolonged contact may cause dryness of the skin.

Eye contact

May cause temporary eye irritation.

Health Warnings

This product has low toxicity. Only large volumes may have adverse impact on human health.

Route of entry

Skin absorption. Ingestion. Skin and/or eye contact.

Medical Considerations

Skin disorders and allergies.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

There are no data on the ecotoxicity of this product.

12.1. Toxicity**12.2. Persistence and degradability**

Degradability

The product is expected to be biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential

No data available on bioaccumulation.

12.4. Mobility in soil

Mobility:

The product contains substances, which are water soluble and may spread in water systems.

12.5. Results of PBT and vPvB assessment**12.6. Other adverse effects**

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

SPO/W201 - METALS PRIMER - RED & GREY

General information

Do not allow to enter drains, sewers or watercourses. Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

13.1. Waste treatment methods

Do not allow runoff to sewer, waterway or ground.

Waste Class

When this coating, in its liquid state, as supplied, becomes a waste, it is categorised as non-hazardous waste, with code 08 01 12 (WATER BASED LIQUID WASTE). Part used containers, not drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 08 01 12 (WATER BASED LIQUID WASTE). If mixed with other wastes, the above waste code may not be applicable. Used containers, drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 02 (plastic packaging) or 15 01 04 (metal packaging).

SECTION 14: TRANSPORT INFORMATION

General The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

Not applicable.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant
No.

14.6. Special precautions for user

No information required.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

SECTION 15: REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Uk Regulatory References

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments.

Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). Control of Substances Hazardous to Health.

Approved Code Of Practice

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply. Dangerous Substances and Explosive Atmospheres Regulations 2002 [L138]

Guidance Notes

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

SPO/W201 - METALS PRIMER - RED & GREY

EU Legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

National Regulations

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689.

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION

Revision Comments

Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 453/2010 Update for CLP labelling.

Issued By	Technical Dept. (P.E.)
Revision Date	14/04/2015
Revision	1
Supersedes date	27/09/2012
SDS No.	11467
Safety Data Sheet Status	Approved.
Date	Date printed _____
Signature	Initials _____

Risk Phrases In Full

R34	Causes burns.
R35	Causes severe burns.
R10	Flammable.
R22	Harmful if swallowed.
R65	Harmful: may cause lung damage if swallowed.
R37	Irritating to respiratory system.
R38	Irritating to skin.
NC	Not classified.
R66	Repeated exposure may cause skin dryness or cracking.
R41	Risk of serious damage to eyes.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67	Vapours may cause drowsiness and dizziness.
R50	Very toxic to aquatic organisms.

Hazard Statements In Full

H318	Causes serious eye damage.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H335	May cause respiratory irritation.
EUH066	Repeated exposure may cause skin dryness or cracking.
H411	Toxic to aquatic life with long lasting effects.
H400	Very toxic to aquatic life.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.