



## SAFETY DATA SHEET

### SPO/W201 - TILE AND MELAMINE PRIMER

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

**Product name** SPO/W201 - TILE AND MELAMINE PRIMER  
**Product number** SPO/W201/1

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Paint.

##### 1.3. Details of the supplier of the safety data sheet

**Supplier** SPECIALIST PAINTS ONLINE  
 3 KIRKBY STREET  
 HULL  
 HU2 0HE  
  
 +44 (0) 1482 222421 (T)  
 sales@specialistpaintsonline.co.uk

**Contact person** Technical Department -, 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri, as above

##### 1.4. Emergency telephone number

**Emergency telephone** +44 (0) 1482 222421 - Specialist Paints Online (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

**SDS No.** 20679 (replaces 11433)

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (EC 1272/2008)

**Physical hazards** Not Classified  
**Health hazards** Not Classified  
**Environmental hazards** Not Classified

##### 2.2. Label elements

**Hazard statements** NC Not Classified

**Precautionary statements** P101 If medical advice is needed, have product container or label at hand.  
 P102 Keep out of reach of children.  
 P262 Do not get in eyes, on skin, or on clothing.  
 P271 Use only outdoors or in a well-ventilated area.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P337+P313 If eye irritation persists: Get medical advice/ attention.  
 P501 Dispose of contents/ container in accordance with national regulations.

## SPO/W201 - TILE AND MELAMINE PRIMER

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

<b>Titanium Dioxide</b>			<b>5-10%</b>
CAS number: 13463-67-7	EC number: 236-675-5	REACH registration number: 01-2119489379-17-xxxx	
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>		
Not Classified	-		
<b>Monopropylene glycol</b>			<b>1-5%</b>
CAS number: 57-55-6	EC number: 200-338-0	REACH registration number: 01-2119456809-23-xxxx	
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>		
Not Classified	-		
<b>Potassium Aluminium Silicate</b>			<b>1-5%</b>
CAS number: 12001-26-2			
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>		
Not Classified	-		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person.
<b>Inhalation</b>	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues. Place unconscious person on their side in the recovery position and ensure breathing can take place.
<b>Ingestion</b>	DO NOT induce vomiting. Get medical attention immediately. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
<b>Skin contact</b>	Remove affected person from source of contamination. Remove contaminated clothing immediately and wash skin with soap and water.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

**General information** Get medical attention promptly if symptoms occur after washing.

#### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes for the doctor** No specific recommendations.

### SECTION 5: Firefighting measures

## SPO/W201 - TILE AND MELAMINE PRIMER

### 5.1. Extinguishing media

**Suitable extinguishing media** Extinguish with foam, carbon dioxide, dry powder or water fog. Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** The product is non-combustible. Toxic and corrosive gases or vapours.

### 5.3. Advice for firefighters

**Protective actions during firefighting** Avoid breathing fire gases or vapours. Avoid the spillage or runoff entering drains, sewers or watercourses. Cool containers exposed to flames with water until well after the fire is out.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet.

### 6.2. Environmental precautions

**Environmental precautions** Avoid discharge into drains or watercourses or onto the ground. Contain spillage with sand, earth or other suitable non-combustible material. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Avoid inhalation of vapours and spray mists. Do not eat, drink or smoke when using the product. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. The Manual Handling Operations Regulations may apply to the handling of containers of this product. To assist employers, the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Store in closed original container at temperatures between 5°C and 25°C. Keep away from heat, sparks and open flame. Protect from freezing and direct sunlight. Keep container tightly closed. Keep containers upright. Store away from the following materials: Oxidising materials. Alkalis. Acids.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SPO/W201 - TILE AND MELAMINE PRIMER

**Usage description** Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible.

### SECTION 8: Exposure Controls/personal protection

#### 8.1. Control parameters

##### Occupational exposure limits

##### **Titanium Dioxide**

Long-term exposure limit (8-hour TWA): WEL 10 mg/m<sup>3</sup> inhalable dust

Long-term exposure limit (8-hour TWA): WEL 4 mg/m<sup>3</sup> respirable dust

##### **Monopropylene glycol**

Long-term exposure limit (8-hour TWA): WEL 150 ppm 10 mg/m<sup>3</sup>

##### **Potassium Aluminium Silicate**

Long-term exposure limit (8-hour TWA): WEL 10 mg/m<sup>3</sup> dust

Long-term exposure limit (8-hour TWA): WEL 0.8 mg/m<sup>3</sup> respirable dust

##### **Barium Sulphate**

Long-term exposure limit (8-hour TWA): 10 mg/m<sup>3</sup> inhalable dust

Long-term exposure limit (8-hour TWA): 4 mg/m<sup>3</sup> respirable dust

##### **Calcium Magnesium Silicate**

Long-term exposure limit (8-hour TWA): WEL 1 mg/m<sup>3</sup>

##### **Hydroxyethyl cellulose**

Long-term exposure limit (8-hour TWA): WEL 10 mg/m<sup>3</sup> total dust

Short-term exposure limit (15-minute): WEL 4 mg/m<sup>3</sup> resp.dust

##### **2-METHOXY-1-METHYLETHYL ACETATE**

Long-term exposure limit (8-hour TWA): WEL 50 ppm 274 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 100 ppm 548 mg/m<sup>3</sup>

Sk

##### **AMMONIA ...%**

Long-term exposure limit (8-hour TWA): WEL 25 ppm 35 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 17 ppm 24 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

#### Titanium Dioxide (CAS: 13463-67-7)

##### **DNEL**

Industry - Inhalation; Long term local effects: 10 mg/m<sup>3</sup>

Consumer - Oral; Long term systemic effects: 700 mg/kg/day

##### **PNEC**

- Fresh water; 0.184 mg/l

- Marine water; 0.0184 mg/l

- Sediment (Freshwater); >=1000 mg/kg

- Sediment (Marinewater); >=100 mg/kg

- Soil; 100 mg/kg

- STP; 100 mg/kg

#### Monopropylene glycol (CAS: 57-55-6)

## SPO/W201 - TILE AND MELAMINE PRIMER

**DNEL** Workers - Inhalation; Long term systemic effects: 168 mg/m<sup>3</sup>  
 Workers - Inhalation; Long term local effects: 10 mg/m<sup>3</sup>  
 Consumer - Inhalation; Long term local effects: 10 mg/m<sup>3</sup>  
 Consumer - Inhalation; Long term systemic effects: 50 mg/m<sup>3</sup>

**PNEC** - Fresh water; 260 mg/l  
 - Marine water; 26 mg/l  
 - Sediment (Freshwater); 572 mg/l  
 - Sediment (Marinewater); 57.2 mg/l  
 - Soil; 50 mg/kg  
 - STP; 20000 mg/l  
 - Intermittent release; 183 mg/l

### 2,2,4 Trimethyl 1,3 Pentanediol Monoisobutyrate (CAS: 25265-77-4)

**DNEL** Workers - Dermal; Long term systemic effects: 13.9 mg/kg/day  
 Workers - Inhalation; Long term systemic effects: 49 mg/m<sup>3</sup>  
 Consumer - Oral; Long term systemic effects: 8.33 mg/kg/day  
 Consumer - Dermal; Long term systemic effects: 8.33 mg/kg/day  
 Consumer - Inhalation; Long term systemic effects: 14.5 mg/m<sup>3</sup>

**PNEC** - Fresh water; 0.015 mg/l  
 - Sediment (Freshwater); 0.78 mg/kg  
 - STP; 7.5 mg/l  
 - Marine water; 0.002 mg/l  
 - Sediment (Marinewater); 0.078 mg/kg  
 - Soil; 0.147 mg/kg

### 2-METHOXY-1-METHYLETHYL ACETATE (CAS: 108-65-6)

**DNEL** Workers - Inhalation; Long term systemic effects: 275 mg/m<sup>3</sup>  
 Workers - Dermal; Long term systemic effects: 796 mg/kg/day  
 Consumer - Inhalation; Long term systemic effects: 33 mg/m<sup>3</sup>  
 Consumer - Dermal; Long term systemic effects: 320 mg/kg/day  
 Consumer - Oral; Long term systemic effects: 36 mg/kg/day

**PNEC** - STP; 100 mg/l  
 - Fresh water; 0.635 mg/l  
 - Soil; 0.29 mg/kg  
 - Sediment; 3.29 mg/kg  
 - Marine water; 0.0635 mg/l  
 - Sediment (Marinewater); 0.329 mg/kg  
 - Intermittent release; 6.35 mg/l

### Diethylene glycol monoethylether (CAS: 111-90-0)

**DNEL** Workers - Dermal; : 83 mg/kg/day  
 Workers - Inhalation; : 61 mg/m<sup>3</sup>  
 Consumer - Oral; : 50 mg/kg/day  
 Consumer - Dermal; : 25 mg/kg/day  
 Consumer - Inhalation; : 37 mg/m<sup>3</sup>

### Hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics (CAS: 64742-48-9)

## SPO/W201 - TILE AND MELAMINE PRIMER

### DNEL

Workers - Inhalation; Long term systemic effects: 1500 mg/m<sup>3</sup>  
 Workers - Dermal; Long term systemic effects: 300 mg/kg/day  
 General population - Inhalation; Long term systemic effects: 900 mg/m<sup>3</sup>  
 General population - Dermal; Long term systemic effects: 300 mg/kg/day  
 General population - Oral; Long term systemic effects: 300 mg/kg/day

### 8.2. Exposure controls

#### Protective equipment



#### Appropriate engineering controls

Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours.

#### Eye/face protection

Wear approved, tight fitting safety glasses where splashing is probable.

#### Hand protection

To protect hands from chemicals, gloves should comply with European Standards EN388 and 374. As a general principle, exposure should be managed by means other than the provision of protective gloves. Manufacturer's performance data suggest that the optimum glove for use should be: Neoprene, nitrile, polyethylene or PVC. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.

#### Other skin and body protection

Wear appropriate clothing to prevent reasonably probable skin contact.

#### Hygiene measures

No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products.

#### Respiratory protection

Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m<sup>3</sup>. In case of inadequate ventilation or risk of inhalation of dust, use suitable respiratory equipment with particle filter (type P2).

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on basic physical and chemical properties

Appearance	Viscous liquid. Coloured liquid.
Colour	White.
Odour	Slight.
Odour threshold	Not determined.
pH	pH (concentrated solution): 8.0 - 9.0
Melting point	Not applicable.
Initial boiling point and range	Not determined.
Flash point	N/A°C
Evaporation rate	Not determined.
Evaporation factor	Not determined.
Flammability (solid, gas)	Not applicable.

## SPO/W201 - TILE AND MELAMINE PRIMER

<b>Upper/lower flammability or explosive limits</b>	Not applicable.
<b>Vapour pressure</b>	Not determined.
<b>Vapour density</b>	heavier than air
<b>Relative density</b>	1.16 @ @ 20°C
<b>Bulk density</b>	Not applicable.
<b>Solubility(ies)</b>	Soluble in water.
<b>Auto-ignition temperature</b>	Not applicable.
<b>Viscosity</b>	2.0 - 3.0 P @ 25°C
<b>Explosive properties</b>	Not applicable.
<b>Explosive under the influence of a flame</b>	Not considered to be explosive.
<b>Oxidising properties</b>	The mixture itself has not been tested but none of the ingredient substances meet the criteria for classification as oxidising.

### 9.2. Other information

**Volatile organic compound** This product contains a maximum VOC content of 45 g/litre.

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

**Reactivity** There are no known reactivity hazards associated with this product.

### 10.2. Chemical stability

**Stability** Stable at normal ambient temperatures and when used as recommended.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** Not determined.

### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Avoid contact with the following materials:  
Acids. Oxidising agents.

### 10.5. Incompatible materials

**Materials to avoid** Strong alkalis. Strong acids. Strong oxidising agents.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

## **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

**Toxicological effects** No data recorded.

### Acute toxicity - oral

**ATE oral (mg/kg)** 13,966.48

## SPO/W201 - TILE AND MELAMINE PRIMER

<b>General information</b>	No specific health hazards known.
<b>Inhalation</b>	No specific health hazards known.
<b>Ingestion</b>	No harmful effects expected from quantities likely to be ingested by accident.
<b>Skin contact</b>	Prolonged contact may cause dryness of the skin.
<b>Eye contact</b>	May cause temporary eye irritation.
<b>Acute and chronic health hazards</b>	This product has low toxicity. Only large quantities are likely to have adverse effects on human health.
<b>Route of exposure</b>	Skin absorption. Ingestion. Skin and/or eye contact.
<b>Medical considerations</b>	Skin disorders and allergies.

### SECTION 12: Ecological Information

**Ecotoxicity** There are no data on the ecotoxicity of this product.

#### 12.1. Toxicity

#### 12.2. Persistence and degradability

**Persistence and degradability** The product is expected to be biodegradable.

#### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

#### 12.4. Mobility in soil

**Mobility** The product contains substances, which are water soluble and may spread in water systems.

#### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

#### 12.6. Other adverse effects

**Other adverse effects** Not determined.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

**General information** Avoid the spillage or runoff entering drains, sewers or watercourses. Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

**Disposal methods** Avoid the spillage or runoff entering drains, sewers or watercourses.

**Waste class** When this coating, in its liquid state, as supplied, becomes a waste, it is categorised as non-hazardous waste, with code 08 01 12 (WATER BASED LIQUID WASTE). Part used containers, not drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 08 01 12 (WATER BASED LIQUID WASTE). If mixed with other wastes, the above waste code may not be applicable. Used containers, drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 02 (plastic packaging) or 15 01 04 (metal packaging).

### SECTION 14: Transport information

**General** The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).



## SPO/W201 - TILE AND MELAMINE PRIMER

### 14.1. UN number

Not applicable.

### 14.2. UN proper shipping name

Not applicable.

**Proper shipping name (ADR/RID)** PAINT OR PAINT RELATED MATERIAL

**Proper shipping name (IMDG)** PAINT OR PAINT RELATED MATERIAL

**Proper shipping name (ICAO)** PAINT OR PAINT RELATED MATERIAL

**Proper shipping name (ADN)** PAINT OR PAINT RELATED MATERIAL

### 14.3. Transport hazard class(es)

Not applicable.

### 14.4. Packing group

Not applicable.

### 14.5. Environmental hazards

**Environmentally hazardous substance/marine pollutant**

No.

### 14.6. Special precautions for user

No information required.

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

**Transport in bulk according to** Not applicable.

**Annex II of MARPOL 73/78 and the IBC Code**

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**National regulations** The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended).

**EU legislation** Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).  
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

**Guidance** Workplace Exposure Limits EH40.

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

## SECTION 16: Other information

**Revision comments** Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 2015/830 Amendment to Section 8.2, recommendations for respiratory protective equipment and hand protection.

**SPO/W201 - TILE AND MELAMINE PRIMER**

**Issued by** Technical Dept. (P.E.)

**Revision date** 09/08/2018

**Revision** 3.2

**Supersedes date** 13/04/2015

**SDS number** 20679

**SDS status** Approved.

**Risk phrases in full** Not classified.  
R10 Flammable.  
R22 Harmful if swallowed.  
R34 Causes burns.  
R35 Causes severe burns.  
R37 Irritating to respiratory system.  
R38 Irritating to skin.  
R41 Risk of serious damage to eyes.  
R50 Very toxic to aquatic organisms.  
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R65 Harmful: may cause lung damage if swallowed.  
R66 Repeated exposure may cause skin dryness or cracking.  
R67 Vapours may cause drowsiness and dizziness.

**Signature** Initials \_\_\_\_\_

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.