



SAFETY DATA SHEET

SPO/W462 - PROTECTIVE COAT FOR LUMINOUS PAINT - CLEAR

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name SPO/W462 - PROTECTIVE COAT FOR LUMINOUS PAINT - CLEAR
Product number SPO/W462/4

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Paint.

1.3. Details of the supplier of the safety data sheet

Supplier SPECIALIST PAINTS ONLINE
 3 KIRKBY STREET
 HULL
 HU2 0HE
 +44 (0) 1482 222421 (T)
 sales@specialistpaintsonline.co.uk

Contact person Sales Department -, 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri, as above

1.4. Emergency telephone number

Emergency telephone +44 (0) 1482 222421 - Specialist Paints Online (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

SDS No. 11418

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified
Health hazards Not Classified
Environmental hazards Not Classified

2.2. Label elements

Hazard statements NC Not Classified

Precautionary statements P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P261 Avoid breathing vapour/ spray.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective clothing and gloves.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P501 Dispose of contents/ container in accordance with national regulations.

SPO/W462 - PROTECTIVE COAT FOR LUMINOUS PAINT - CLEAR

Supplemental label information Contains 1,2-benzisothiazol-3(3H)-one. May produce an allergic reaction.

Supplementary precautionary statements P403+P235 Store in a well-ventilated place. Keep cool.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Monopropylene glycol			1-5%
CAS number: 57-55-6	EC number: 200-338-0	REACH registration number: 01-2119456809-23-xxxx	
Classification	Classification (67/548/EEC or 1999/45/EC)		
Not Classified	-		
1,2-BENZISOTHIAZOL-3(2H)-ONE			<0.05%
CAS number: 2634-33-5	EC number: 220-120-9	REACH registration number: 01-2120761540-60-XXXX	
M factor (Acute) = 1			
Classification	Classification (67/548/EEC or 1999/45/EC)		
Acute Tox. 4 - H302	Xn;R22 R43 Xi;R38,R41 N;R50		
Skin Irrit. 2 - H315			
Eye Dam. 1 - H318			
Skin Sens. 1 - H317			
Aquatic Acute 1 - H400			

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person.
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues. Place unconscious person on their side in the recovery position and ensure breathing can take place.
Ingestion	DO NOT induce vomiting. Get medical attention immediately. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing immediately and wash skin with soap and water.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information Get medical attention promptly if symptoms occur after washing.

SPO/W462 - PROTECTIVE COAT FOR LUMINOUS PAINT - CLEAR

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog. Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards The product is non-combustible. Toxic and corrosive gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours. Avoid the spillage or runoff entering drains, sewers or watercourses. Cool containers exposed to flames with water until well after the fire is out.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Contain spillage with sand, earth or other suitable non-combustible material. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Avoid inhalation of vapours and spray mists. Do not eat, drink or smoke when using the product. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. The Manual Handling Operations Regulations may apply to the handling of containers of this product. To assist employers, the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight.

7.2. Conditions for safe storage, including any incompatibilities

SPO/W462 - PROTECTIVE COAT FOR LUMINOUS PAINT - CLEAR

Storage precautions Store in closed original container at temperatures between 5°C and 25°C. Keep away from heat, sparks and open flame. Protect from freezing and direct sunlight. Keep container tightly closed. Keep containers upright. Store away from the following materials: Oxidising materials. Alkalis. Acids.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

Usage description Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Monopropylene glycol

Long-term exposure limit (8-hour TWA): WEL 150 ppm 10 mg/m³

2-(2-BUTOXYETHOXY)ETHANOL

Long-term exposure limit (8-hour TWA): WEL 10 ppm 67.5 mg/m³

Short-term exposure limit (15-minute): WEL 15 ppm 101.2 mg/m³

AMMONIA ...%

Long-term exposure limit (8-hour TWA): WEL 25 ppm 35 mg/m³

Short-term exposure limit (15-minute): WEL 17 ppm 24 mg/m³

SODIUM HYDROXIDE

Short-term exposure limit (15-minute): WEL 2 mg/m³

2,6-Di-tert-butyl-p-cresol

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³

WEL = Workplace Exposure Limit

Monopropylene glycol (CAS: 57-55-6)

DNEL Workers - Inhalation; Long term systemic effects: 168 mg/m³
Workers - Inhalation; Long term local effects: 10 mg/m³
Consumer - Inhalation; Long term local effects: 10 mg/m³
Consumer - Inhalation; Long term systemic effects: 50 mg/m³

PNEC - Fresh water; 260 mg/l
- marine water; 26 mg/l
- Sediment (Freshwater); 572 mg/l
- Sediment (Marinewater); 57.2 mg/l
- Soil; 50 mg/kg
- STP; 20000 mg/l
- Intermittent release; 183 mg/l

2,2,4 Trimethyl 1,3 Pentanediol Monoisobutyrate (CAS: 25265-77-4)

DNEL Workers - Dermal; Long term systemic effects: 13.9 mg/kg/day
Workers - Inhalation; Long term systemic effects: 49 mg/m³
Consumer - Oral; Long term systemic effects: 8.33 mg/kg/day
Consumer - Dermal; Long term systemic effects: 8.33 mg/kg/day
Consumer - Inhalation; Long term systemic effects: 14.5 mg/m³

SPO/W462 - PROTECTIVE COAT FOR LUMINOUS PAINT - CLEAR

PNEC	- Fresh water; 0.015 mg/l
	- Sediment (Freshwater); 0.78 mg/kg
	- STP; 7.5 mg/l
	- marine water; 0.002 mg/l
	- Sediment (Marinewater); 0.078 mg/kg
	- Soil; 0.147 mg/kg

2-(2-BUTOXYETHOXY)ETHANOL (CAS: 112-34-5)

DNEL	Workers - Inhalation; Short term local effects: 101.2 mg/m ³
	Workers - Dermal; Long term systemic effects: 83 mg/kg/day
	Workers - Inhalation; Long term systemic effects: 67.5 mg/m ³
	Workers - Inhalation; Long term local effects: 67.5 mg/m ³
	Consumer - Inhalation; Short term local effects: 60.7 mg/m ³
	Consumer - Dermal; Long term systemic effects: 50 mg/kg/day
	Consumer - Inhalation; Long term systemic effects: 40.5 mg/m ³
	Consumer - Oral; Long term systemic effects: 5 mg/kg/day
Consumer - Inhalation; Long term local effects: 40.5 mg/m ³	

PNEC	- Fresh water; 1.1 mg/l
	- marine water; 0.11 mg/l
	- Intermittent release; 11 mg/l
	- STP; 200 mg/l
	- Sediment (Freshwater); 4.4 mg/kg
	- Sediment (Marinewater); 0.44 mg/kg
	- Soil; 0.32 mg/kg

2,6-Di-tert-butyl-p-cresol (CAS: 128-37-0)

DNEL	Industry - Dermal; : 0.5 mg/kg/day
	Industry - Inhalation; : 3.5 mg/kg/day

PNEC	- Fresh water; 0.000199 mg/l
	- Sediment; 0.0996 mg/l
	- Soil; 0.04769 mg/l
	- marine water; 0.0000199 mg/l

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours.

Eye/face protection

Wear approved, tight fitting safety glasses where splashing is probable.

SPO/W462 - PROTECTIVE COAT FOR LUMINOUS PAINT - CLEAR

Hand protection	To protect hands from chemicals, gloves should comply with European Standards EN388 and 374. As a general principle, exposure should be managed by means other than the provision of protective gloves. Manufacturer's performance data suggest that the optimum glove for use should be: Neoprene, nitrile, polyethylene or PVC. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.
Other skin and body protection	Wear appropriate clothing to prevent reasonably probable skin contact.
Hygiene measures	No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products.
Respiratory protection	Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m ³ . In case of inadequate ventilation or risk of inhalation of dust, use suitable respiratory equipment with particle filter (type P2).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	White Viscous liquid.
Colour	Dries clear
Odour	Mild.
Odour threshold	Not determined.
Melting point	Not applicable.
Initial boiling point and range	Not determined.
Flash point	Not applicable.
Evaporation rate	Not determined.
Evaporation factor	Not determined.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Not applicable.
Vapour pressure	Not determined.
Vapour density	Not determined.
Relative density	1.05 approx. @ @ 20 C°C
Bulk density	Not applicable.
Solubility(ies)	Miscible with water
Auto-ignition temperature	Not applicable.
Viscosity	3.5 (Rotothinner) P @ 25 C°C
Explosive properties	Not applicable.
Explosive under the influence of a flame	Not considered to be explosive.

SPO/W462 - PROTECTIVE COAT FOR LUMINOUS PAINT - CLEAR

Oxidising properties The mixture itself has not been tested but none of the ingredient substances meet the criteria for classification as oxidising.

9.2. Other information

Volatile organic compound EU: (cat A/i): 140 g/l 2010. This product contains a maximum VOC content of 36 g/litre.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not determined.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Acids. Oxidising agents.

10.5. Incompatible materials

Materials to avoid Strong alkalis. Strong acids. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No data recorded.

General information No specific health hazards known.

Inhalation No specific health hazards known.

Ingestion No harmful effects expected from quantities likely to be ingested by accident.

Skin contact Prolonged contact may cause dryness of the skin.

Eye contact May cause temporary eye irritation.

Acute and chronic health hazards This product has low toxicity. Only large quantities are likely to have adverse effects on human health.

Route of exposure Skin absorption. Ingestion. Skin and/or eye contact.

Medical considerations Skin disorders and allergies.

Toxicological information on ingredients.

Monopropylene glycol

Acute toxicity - oral

Acute toxicity oral (LD₅₀) 20,000.0
mg/kg)

SPO/W462 - PROTECTIVE COAT FOR LUMINOUS PAINT - CLEAR

Species Rat
ATE oral (mg/kg) 20,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,100.0

Species Rabbit
ATE dermal (mg/kg) 2,100.0

Skin corrosion/irritation

Skin corrosion/irritation Not irritating.

Serious eye damage/irritation

Serious eye damage/irritation Not irritating.

Respiratory sensitisation

Respiratory sensitisation Not sensitising.

Skin sensitisation

Skin sensitisation Not sensitising.

1,2-BENZISOTHIAZOL-3(2H)-ONE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 1,193.0

Species Rat
ATE oral (mg/kg) 1,193.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 4,115.0

Species Rat
ATE dermal (mg/kg) 4,115.0

SECTION 12: Ecological information

Ecotoxicity There are no data on the ecotoxicity of this product.

12.1. Toxicity

Ecological information on ingredients.

Monopropylene glycol

Acute aquatic toxicity

Acute toxicity - fish LC50, 96 hours: 40613 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates EC₅₀, > 48 hours: 43500 mg/l, Daphnia magna

SPO/W462 - PROTECTIVE COAT FOR LUMINOUS PAINT - CLEAR

Acute toxicity - aquatic plants	EC ₅₀ , 96 hours: 19000 mg/l, Scenedesmus subspicatus EC ₅₀ , 96 hours: 19000 mg/l, Freshwater algae
Acute toxicity - microorganisms	NOEC, 18 hours: 20000 mg/l, Activated sludge

12.2. Persistence and degradability

Persistence and degradability The product is expected to be biodegradable.

Ecological information on ingredients.

Monopropylene glycol

Persistence and degradability	The product is readily biodegradable.
Biodegradation	- Degradation 81%: > 28 days - Degradation 96%: 64 days

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Ecological information on ingredients.

Monopropylene glycol

Bioaccumulative potential	The product is not bioaccumulating. BCF: < 100,
Partition coefficient	log Pow: 1.07

12.4. Mobility in soil

Mobility The product contains substances, which are water soluble and may spread in water systems.

Ecological information on ingredients.

Monopropylene glycol

Mobility	The product contains volatile organic compounds (VOCs) which have a photochemical ozone creation potential.
Henry's law constant	0.00566 atm m ³ /mol @ @ 12 °C°C

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

Monopropylene glycol

Results of PBT and vPvB assessment	This substance is not classified as PBT or vPvB according to current EU criteria.
---	---

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

SPO/W462 - PROTECTIVE COAT FOR LUMINOUS PAINT - CLEAR

General information	Avoid the spillage or runoff entering drains, sewers or watercourses. Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
Disposal methods	Avoid the spillage or runoff entering drains, sewers or watercourses.
Waste class	When this coating, in its liquid state, as supplied, becomes a waste, it is categorised as non-hazardous waste, with code 08 01 12 (WATER BASED LIQUID WASTE). Part used containers, not drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 08 01 12 (WATER BASED LIQUID WASTE). If mixed with other wastes, the above waste code may not be applicable. Used containers, drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 02 (plastic packaging) or 15 01 04 (metal packaging).

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

UN No. (ADR/RID) 1263

14.2. UN proper shipping name

Not applicable.

Proper shipping name (ADR/RID) PAINT OR PAINT RELATED MATERIAL

Proper shipping name (IMDG) PAINT OR PAINT RELATED MATERIAL

Proper shipping name (ICAO) PAINT OR PAINT RELATED MATERIAL

Proper shipping name (ADN) PAINT OR PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

Not applicable.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

No information required.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

SPO/W462 - PROTECTIVE COAT FOR LUMINOUS PAINT - CLEAR

National regulations	The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended).
EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Guidance	Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet	ATE: Acute Toxicity Estimate. ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. CAS: Chemical Abstracts Service. DNEL: Derived No Effect Level. GHS: Globally Harmonized System. ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air. IMDG: International Maritime Dangerous Goods. LD ₅₀ : Lethal Dose to 50% of a test population (Median Lethal Dose). PBT: Persistent, Bioaccumulative and Toxic substance. REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006. PNEC: Predicted No Effect Concentration. RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail. SVHC: Substances of Very High Concern. vPvB: Very Persistent and Very Bioaccumulative. cATpE: Converted Acute Toxicity Point Estimate. EC ₅₀ : 50% of maximal Effective Concentration.
Classification abbreviations and acronyms	Aquatic Acute = Hazardous to the aquatic environment (acute) Aquatic Chronic = Hazardous to the aquatic environment (chronic) Asp. Tox. = Aspiration hazard Carc. = Carcinogenicity Eye Dam. = Serious eye damage Eye Irrit. = Eye irritation Resp. Sens. = Respiratory sensitisation Skin Irrit. = Skin irritation Skin Sens. = Skin sensitisation STOT SE = Specific target organ toxicity-single exposure STOT RE = Specific target organ toxicity-repeated exposure
Revision comments	Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 2015/830
Issued by	Technical Dept. (P.E.)
Revision date	02/04/2019
Revision	3.0

SPO/W462 - PROTECTIVE COAT FOR LUMINOUS PAINT - CLEAR

Supersedes date	04/12/2018
SDS number	11418
SDS status	Approved.
Hazard statements in full	H302 Harmful if swallowed. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H400 Very toxic to aquatic life.
Signature	Initials _____

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.